



F21 Lite

Fingerprint time attendance and access control terminal

F21 Lite is a time attendance and access control terminal with advanced BioID technology. It possesses outstandingly high identification rate towards dry, wet and rough finger, Anti-Highlight and Side-Beams minimise the interference occurred during fingerprint verification and Infrared technology enables the device to function automatically when fingerprints are detected, reducing unnecessary electrical usage thus saving energy.

In addition, with the brand new ZMM220 hardware platform, its clock rate can attain 1.2GHZ. Such speedy hardware platform and fingerprint algorithm greatly enhance the speed of fingerprint verification.

Features

- · 2.4-inch TFT color screen
- BioID fingerprint reader with Anti-Interference Technology and Sensor-Activation function.
- Multiple Verification Modes: Multiverification methods (card is optional) providing user various choices
- Full Access Control Features:
 Anti-passback, access control interface for 3rd party electric lock, door sensor, exit button, alarm and doorbell
- Built-in auxiliary input with enhanced flexibility to link with wired detector or emergency switch
- Wireless door bell (Optional)

Specifications

Display 2.4-inch TFT LCD Color Screen Fingerprint Capacity 3000 Card Capacity 5000(Optional) ID or mifare card Transaction Capacity 100,000 Sensor BioID Sensor Algorithm Version ZKFinger VX10.0 Communication RS232/485, TCP/IP, USB-host
Card Capacity 5000(Optional) ID or mifare card Transaction Capacity 100,000 Sensor BioID Sensor Algorithm Version ZKFinger VX10.0
Transaction Capacity 100,000 Sensor BioID Sensor Algorithm Version ZKFinger VX10.0
Sensor BioID Sensor Algorithm Version ZKFinger VX10.0
Algorithm Version ZKFinger VX10.0
Communication RS232/485. TCP/IP. USB-host
Access Control Interface 3rd Party Electric Lock, Door Sensor, Exit Button, Alarm, Doorbell
Wiegand Signal Input, Output, SRB
Aux. Input 1ea for linkage function
Functions DST, Automatic Status Switch, Anti-passback, Scheduled-Bell, Printer (Optional)
Power Supply 12V DC,3A
Operating Temperature 0 °C- 45 °C
Operating Humidity 20%-80%

Optional Accessories







Exit Button



Electric Lock



Alarm




Sensor



Wireless Door Bell

Configuration



Dimensions (mm)

